



# LED LINEAR TUBES

| WATTS  | BOOK ITEM # | DESCRIPTION                             | SPEC SHEET  | CCT                        | LUMENS | TRAD. EQUIV. | CASE      |
|--|-------------|---|---|----------------------------|--------|--------------|-----------|
| <b>LED COOLER LIGHTS • 120V</b>  |             |   |   |                            |        |              |           |
|  | 20          | DL16783945                              | 5' V-COOLER/20W/40K/CL/270° - <b>DLC®</b>             | <a href="#">SPEC SHEET</a> | 4000K  | 2400         | T8/T12 20 |
|  |             | DL16883946                              | 5' V-COOLER/20W/50K/CL/270° - <b>DLC®</b>             | <a href="#">SPEC SHEET</a> | 5000K  | 2400         | T8/T12 20 |
|  | 22          | DL16983948                              | 6' V-COOLER/22W/40K/CL/270° - <b>DLC®</b>             | <a href="#">SPEC SHEET</a> | 4000K  | 2640         | T8/T12 20 |
|  |             | DL17083949                              | 6' V-COOLER/22W/50K/CL/270° - <b>DLC®</b>             | <a href="#">SPEC SHEET</a> | 5000K  | 2640         | T8/T12 20 |
| <b>LED DIRECT REPLACEMENT - UL TYPE A</b>  |             |   |   |                            |        |              |           |
| <b>T5/T5HO/MINI BI PIN</b> <i>MT = Metal End Caps</i>                                |             |   |   |                            |        |              |           |
|  | 25          | DL17190449                              | 46" 25WT5/40K/FR - <b>DLC®</b>                        | <a href="#">SPEC SHEET</a> | 4000K  | 3500         | T5 25     |
|  |             | DL17290450                              | 46" 25WT5/50K/FR - <b>DLC®</b>                        | <a href="#">SPEC SHEET</a> | 5000K  | 3500         | T5 25     |
|  | 25.5        | DL17391319                              | 46" 25.5WT5/50K/FR/SAFETY COATED/V5 - <b>DLC®</b>     | <a href="#">SPEC SHEET</a> | 5000K  | 3600         | T5 25     |
| <b>T8/MED BI PIN</b> <i>MT = Metal End Caps</i>                                      |             |   |   |                            |        |              |           |
|  | 9           | DL17491324                              | 2' 9WT8/40K/FR/V5 - <b>DLC®</b>                       | <a href="#">SPEC SHEET</a> | 4000K  | 1475         | T8 25     |
|  |             | DL17591325                              | 2' 9WT8/50K/FR/V5 - <b>DLC®</b>                       | <a href="#">SPEC SHEET</a> | 5000K  | 1500         | T8 25     |
|  | 10          | DL17690728                              | 3' 10WT8/40K/FR/V4 - <b>DLC®</b>                      | <a href="#">SPEC SHEET</a> | 4000K  | 1450         | T8 25     |
|  |             | DL17790729                              | 3' 10WT8/50K/FR/V4 - <b>DLC®</b>                      | <a href="#">SPEC SHEET</a> | 5000K  | 1450         | T8 25     |
|  |             | DL17891828                              | 3' 10WT8/50K/FR/V5                                    | <a href="#">SPEC SHEET</a> | 5000K  | 1450         | T8 25     |
|  | 10.5        | DL17991030                              | 4' 10.5WT8/35K/FR/SAFETY COATED/V5 - <b>CEE/DLC®</b>  | <a href="#">SPEC SHEET</a> | 3500K  | 1708         | T8 25     |
|  |             | DL18091032                              | 4' 10.5WT8/50K/FR/SAFETY COATED/V5 - <b>CEE/DLC®</b>  | <a href="#">SPEC SHEET</a> | 5000K  | 1806         | T8 25     |
|  | 11          | DL18191831                              | 4' 11WT8/40K/FR/V2                                    | <a href="#">SPEC SHEET</a> | 4000K  | 1800         | T8 25     |
|  |             | DL18291045                              | 4' 12WT8/50K/FR - <b>DLC® MT</b>                      | <a href="#">SPEC SHEET</a> | 5000K  | 1800         | T8 25     |
|  | 13          | DL18391460                              | 4' 13WT8/35K/FR                                       | <a href="#">SPEC SHEET</a> | 3500K  | 1800         | T8 25     |
|  |             | DL18491461                              | 4' 13WT8/40K/FR                                       | <a href="#">SPEC SHEET</a> | 4000K  | 1800         | T8 25     |
|  |             | DL18591462                              | 4' 13WT8/50K/FR                                       | <a href="#">SPEC SHEET</a> | 5000K  | 1800         | T8 25     |
|  |             | DL18691289                              | 4' 13WT8/35K/FR/V5 - <b>CEE/DLC® MT</b>               | <a href="#">SPEC SHEET</a> | 3500K  | 1800         | T8 25     |
|  |             | DL18791313                              | 4' 13WT8/35K/FR/SAFETY COATED/V5 - <b>CEE/DLC®</b>    | <a href="#">SPEC SHEET</a> | 3500K  | 1950         | T8 25     |
|  |             | DL18891315                              | 4' 13WT8/50K/FR/SAFETY COATED/V5 - <b>CEE/DLC®</b>    | <a href="#">SPEC SHEET</a> | 5000K  | 2000         | T8 25     |
|  |             | DL18991400                              | 4' 13WT8/40K/FR/SAFETY COATED/V5 - <b>CEE/DLC® MT</b> | <a href="#">SPEC SHEET</a> | 4000K  | 2000         | T8 25     |
|  | 15          | DL19091047                              | 4' 15WT8/40K/FR - <b>DLC® MT</b>                      | <a href="#">SPEC SHEET</a> | 4000K  | 2200         | T8 25     |
|  |             | DL19191048                              | 4' 15WT8/50K/FR - <b>DLC® MT</b>                      | <a href="#">SPEC SHEET</a> | 5000K  | 2200         | T8 25     |
|  |             | DL19291305                              | 4' 15WT8/35K/FR/V5 - <b>CEE/DLC®</b>                  | <a href="#">SPEC SHEET</a> | 3500K  | 2250         | T8 25     |
|  |             | DL19391309                              | 4' 15WT8/35K/FR/V5 - <b>CEE/DLC® MT</b>               | <a href="#">SPEC SHEET</a> | 3500K  | 2250         | T8 25     |
| 17   | DL19491294  | 4' 17WT8/50K/FR/V5 - <b>CEE/DLC® MT</b> | <a href="#">SPEC SHEET</a>                            | 5000K                      | 2400   | T8 25        |           |
| <b>T8/SINGLE PIN</b>   |             |   |   |                            |        |              |           |
|  | 24          | DL19591420                              | 8' 24WT8/50K/FR/SAFETY COATED - <b>DLC®</b>           | <a href="#">SPEC SHEET</a> | 5000K  | 3500         | T8 8      |
|  | 42          | DL19691423                              | 8' 42WT8/50K/FR/SAFETY COATED - <b>DLC®</b>           | <a href="#">SPEC SHEET</a> | 5000K  | 5800         | T8 8      |
| <b>LED DIRECT REPLACEMENT OR DIRECT WIRE • 120-277V - UL TYPE A &amp; B</b>          |             |   |   |                            |        |              |           |
|  | 14          | DL19791466                              | 4' 14WT8/35K/FR - <b>DLC®</b>                         | <a href="#">SPEC SHEET</a> | 3500K  | 1800         | T8 25     |
|  |             | DL19891467                              | 4' 14WT8/40K/FR - <b>DLC®</b>                         | <a href="#">SPEC SHEET</a> | 4000K  | 1800         | T8 25     |
|  |             | DL19991468                              | 4' 14WT8/50K/FR - <b>DLC®</b>                         | <a href="#">SPEC SHEET</a> | 5000K  | 1800         | T8 25     |
|  |             | DL20090417                              | 4' 14WT8/35K/FR/SAFETY COATED/V5 - <b>CEE/DLC®</b>    | <a href="#">SPEC SHEET</a> | 3500K  | 2150         | T8 25     |
|  |             | DL20190418                              | 4' 14WT8/40K/FR/SAFETY COATED/V5 - <b>CEE/DLC®</b>    | <a href="#">SPEC SHEET</a> | 4000K  | 2100         | T8 25     |
|  |             | DL20290419                              | 4' 14WT8/50K/FR/SAFETY COATED/V5 - <b>CEE/DLC®</b>    | <a href="#">SPEC SHEET</a> | 5000K  | 2200         | T8 25     |
| <b>LED DIRECT REPLACEMENT OR DIRECT WIRE • 120-277V - UL TYPE A &amp; B (cont'd)</b> |             |   |   |                            |        |              |           |
| <b>T8/UI 5/8"</b>  |             |   |   |                            |        |              |           |

DIMM = DIMMABLE / **ES®** = ENERGY STAR®  
 FOR EXACT PART NUMBERS PLEASE CONTACT FACTORY

LED LINEAR TUBES

| WATTS        | BOOK ITEM # | DESCRIPTION                   | SPEC SHEET                 | CCT   | LUMENS | TRAD. EQUIV. | CASE |
|--------------|-------------|-------------------------------|----------------------------|-------|--------|--------------|------|
| 15           | DL20390884  | LED 15WT8/U 1 5/8" /50K/FR    | <a href="#">SPEC SHEET</a> | 5000K | 2200   | T8/U1        | 24   |
| <b>T8/U6</b> |             |                               |                            |       |        |              |      |
| 13           | DL20490439  | 13WT8/U6/35K/FR - <b>DLC®</b> | <a href="#">SPEC SHEET</a> | 3500K | 1950   | T8/U6        | 12   |
|              | DL20590440  | 13WT8/U6/40K/FR - <b>DLC®</b> | <a href="#">SPEC SHEET</a> | 4000K | 1900   | T8/U6        | 12   |
|              | DL20690441  | 13WT8/U6/50K/FR - <b>DLC®</b> | <a href="#">SPEC SHEET</a> | 5000K | 2000   | T8/U6        | 12   |

LED DIRECT WIRE / SINGLE END CONNECTION - UL TYPE B

T5/T5HO/MINI BI PIN • 120-277V

|    |            |                                   |                            |       |      |    |    |
|----|------------|-----------------------------------|----------------------------|-------|------|----|----|
| 13 | DL20790428 | 46" 13WT5/T6/40K/FR - <b>DLC®</b> | <a href="#">SPEC SHEET</a> | 4000K | 1650 | T5 | 25 |
|    | DL20890429 | 46" 13WT5/T6/50K/FR - <b>DLC®</b> | <a href="#">SPEC SHEET</a> | 5000K | 1700 | T5 | 25 |
| 25 | DL20990433 | 46" 25WT5/T6/35K/FR - <b>DLC®</b> | <a href="#">SPEC SHEET</a> | 3500K | 3200 | T5 | 25 |
|    | DL21090434 | 46" 25WT5/T6/40K/FR - <b>DLC®</b> | <a href="#">SPEC SHEET</a> | 4000K | 3300 | T5 | 25 |
|    | DL21190435 | 46" 25WT5/T6/50K/FR - <b>DLC®</b> | <a href="#">SPEC SHEET</a> | 5000K | 3400 | T5 | 25 |

T8/MED BI PIN • 120-277V

|      |            |  |                            |       |      |    |    |
|------|------------|--|----------------------------|-------|------|----|----|
| 9    | DL21291286 | 2' 9WT8/40K/FR/V5 - <b>DLC®</b>                      | <a href="#">SPEC SHEET</a> | 4000K | 1200 | T8 | 25 |
|      | DL21391287 | 2' 9WT8/50K/FR/V5 - <b>DLC®</b>                      | <a href="#">SPEC SHEET</a> | 5000K | 1250 | T8 | 25 |
| 12   | DL21490735 | 3' 12WT8/30K/FR/V4 - <b>DLC®</b>                     | <a href="#">SPEC SHEET</a> | 3000K | 1400 | T8 | 25 |
|      | DL21590736 | 3' 12WT8/35K/FR/V4 - <b>DLC®</b>                     | <a href="#">SPEC SHEET</a> | 3500K | 1400 | T8 | 25 |
|      | DL21690737 | 3' 12WT8/40K/FR/V4 - <b>DLC®</b>                     | <a href="#">SPEC SHEET</a> | 4000K | 1450 | T8 | 25 |
|      | DL21790738 | 3' 12WT8/50K/FR/V4 - <b>DLC®</b>                     | <a href="#">SPEC SHEET</a> | 5000K | 1450 | T8 | 25 |
| 10.5 | DL21891027 | 4' 10.5WT8/35K/FR - <b>CEE/DLC®</b>                  | <a href="#">SPEC SHEET</a> | 3500K | 1650 | T8 | 25 |
|      | DL21991028 | 4' 10.5WT8/40K/FR - <b>CEE/DLC®</b>                  | <a href="#">SPEC SHEET</a> | 4000K | 1700 | T8 | 25 |
|      | DL22091029 | 4' 10.5WT8/50K/FR - <b>CEE/DLC®</b>                  | <a href="#">SPEC SHEET</a> | 5000K | 1700 | T8 | 25 |
| 12   | DL22190578 | 4' 12WT8/30K/FR/V4 - <b>CEE/DLC®</b>                 | <a href="#">SPEC SHEET</a> | 3000K | 1700 | T8 | 25 |
|      | DL22290593 | 4' 12WT8/35K/FR/V4 - <b>CEE/DLC®</b>                 | <a href="#">SPEC SHEET</a> | 3500K | 1700 | T8 | 25 |
|      | DL22390567 | 4' 12WT8/40K/FR/V4 - <b>CEE/DLC®</b>                 | <a href="#">SPEC SHEET</a> | 4000K | 1800 | T8 | 25 |
|      | DL22490568 | 4' 12WT8/50K/FR/V4 - <b>CEE/DLC®</b>                 | <a href="#">SPEC SHEET</a> | 5000K | 1800 | T8 | 25 |
| 14   | DL22591190 | 4' 14WT8/35K/FR/V2 - <b>CEE/DLC®</b>                 | <a href="#">SPEC SHEET</a> | 3500K | 1800 | T8 | 25 |
|      | DL22691191 | 4' 14WT8/40K/FR/V2 - <b>CEE/DLC®</b>                 | <a href="#">SPEC SHEET</a> | 4000K | 1800 | T8 | 25 |
|      | DL22791192 | 4' 14WT8/50K/FR/V2 - <b>CEE/DLC®</b>                 | <a href="#">SPEC SHEET</a> | 5000K | 1800 | T8 | 25 |
| 14.5 | DL22891301 | 4' 14.5WT8/50K/CL/SAFETY COATED/V5 - <b>CEE/DLC®</b> | <a href="#">SPEC SHEET</a> | 5000K | 2100 | T8 | 25 |
| 15   | DL22991281 | 4' 15WT8/35K/FR/SAFETY COATED/V5 - <b>CEE/DLC®</b>   | <a href="#">SPEC SHEET</a> | 3500K | 1900 | T8 | 25 |
|      | DL23091282 | 4' 15WT8/40K/FR/SAFETY COATED/V5 - <b>CEE/DLC®</b>   | <a href="#">SPEC SHEET</a> | 4000K | 2000 | T8 | 25 |
|      | DL23191283 | 4' 15WT8/50K/FR/SAFETY COATED/V5 - <b>CEE/DLC®</b>   | <a href="#">SPEC SHEET</a> | 5000K | 2100 | T8 | 25 |
|      | DL23291416 | 4' 15WT8/ <b>BLUE</b> /FROST/SAFETY COATED           | <a href="#">SPEC SHEET</a> | -     | 1800 | T8 | 25 |
| 16   | DL23391463 | 4' 16WT8/35K/FR                                      | <a href="#">SPEC SHEET</a> | 3500K | 1600 | T8 | 25 |
|      | DL23491464 | 4' 16WT8/40K/FR                                      | <a href="#">SPEC SHEET</a> | 4000K | 1600 | T8 | 25 |
|      | DL23591465 | 4' 16WT8/50K/FR                                      | <a href="#">SPEC SHEET</a> | 5000K | 1600 | T8 | 25 |
| 17   | DL23691193 | 4' 17WT8/35K/FR/V2 - <b>CEE/DLC®</b>                 | <a href="#">SPEC SHEET</a> | 3500K | 2200 | T8 | 25 |
|      | DL23791194 | 4' 17WT8/40K/FR/V2 - <b>CEE/DLC®</b>                 | <a href="#">SPEC SHEET</a> | 4000K | 2200 | T8 | 25 |
|      | DL23891195 | 4' 17WT8/50K/FR/V2 - <b>CEE/DLC®</b>                 | <a href="#">SPEC SHEET</a> | 5000K | 2200 | T8 | 25 |

T8/DIMMABLE • 120V

|      |            |   |                            |       |      |    |    |
|------|------------|---|----------------------------|-------|------|----|----|
| 13.5 | DL23990468 | 4' 13.5WT8/40K/FR/DIMMABLE/V5 - <b>CEE/DLC®</b> | <a href="#">SPEC SHEET</a> | 4000K | 1800 | T8 | 25 |
|      | DL24090469 | 4' 13.5WT8/50K/FR/DIMMABLE/V5 - <b>CEE/DLC®</b> | <a href="#">SPEC SHEET</a> | 5000K | 1800 | T8 | 25 |

ACCESSORY

|   |            |  |                            |  |  |  |    |
|---|------------|--|----------------------------|--|--|--|----|
| 5 | DL24190405 | 5W/90MIN EMERGENCY DRIVER FOR SELECT T8 DIRECT WIRE LAMPS 120/277V - <b>T20C</b> | <a href="#">SPEC SHEET</a> |  |  |  | 25 |
|---|------------|--|----------------------------|--|--|--|----|

LED DIRECT WIRE / DOUBLE END CONNECTION • 120-277V - UL TYPE B

T5/T5HO/MINI BI PIN

|   |            |                              |                            |       |      |    |    |
|---|------------|------------------------------|----------------------------|-------|------|----|----|
| 9 | DL24290425 | 2' 9WT5/T6/50K/FR/DUAL POWER | <a href="#">SPEC SHEET</a> | 5000K | 1200 | T5 | 25 |
|---|------------|------------------------------|----------------------------|-------|------|----|----|

T8/MED BI PIN

|      |            |   |                            |       |      |    |    |
|------|------------|---|----------------------------|-------|------|----|----|
|      | DL24391472 | 4' 10.5WT8/40K/FR/DUAL POWER - <b>DLC®</b>                      | <a href="#">SPEC SHEET</a> | 4000K | 1738 | T8 | 25 |
|      | DL24491473 | 4' 10.5WT8/50K/FR/DUAL POWER - <b>DLC®</b>                      | <a href="#">SPEC SHEET</a> | 5000K | 1767 | T8 | 25 |
| 11.5 | DL24591274 | 4' 11.5WT8/35K/FR/DUAL POWER/SAFETY COATED/V5 - <b>DLC®</b>     | <a href="#">SPEC SHEET</a> | 3500K | 1650 | T8 | 25 |
|      | DL24691275 | 4' 11.5WT8/40K/FR/DUAL POWER/SAFETY COATED/V5 - <b>CEE/DLC®</b> | <a href="#">SPEC SHEET</a> | 4000K | 1750 | T8 | 25 |
| 14   | DL24791138 | 4' 14WT8/35K/FR/DUAL POWER - <b>CEE/DLC®</b>                    | <a href="#">SPEC SHEET</a> | 3500K | 1800 | T8 | 25 |

DIMM = DIMMABLE / ES® = ENERGY STAR®  
FOR EXACT PART NUMBERS PLEASE CONTACT FACTORY



# LED LINEAR TUBES

| WATTS  | BOOK ITEM # | DESCRIPTION   | SPEC SHEET                 | CCT   | LUMENS | TRAD. EQUIV. | CASE |
|--|-------------|---|----------------------------|-------|--------|--------------|------|
|  | DL24891139  | 4' 14WT8/40K/FR/DUAL POWER - <b>CEE/DLC®</b>                    | <a href="#">SPEC SHEET</a> | 4000K | 1800   | T8           | 25   |
| <b>LED DIRECT WIRE / DOUBLE END CONNECTION • 120-277V - UL TYPE B (cont'd)</b> |             |   |                            |       |        |              |      |
|  | DL24991140  | 4' 14WT8/50K/FR/DUAL POWER - <b>CEE/DLC®</b>                    | <a href="#">SPEC SHEET</a> | 5000K | 1800   | T8           | 25   |
|  | DL25091487  | 4' 14WT8/40K/FR/DUAL POWER/SAFETY COATED/V6 - <b>DLC®</b>       | <a href="#">SPEC SHEET</a> | 4000K | 1800   | T8           | 25   |
|  | DL25191488  | 4' 14WT8/50K/FR/DUAL POWER/SAFETY COATED/V6 - <b>DLC®</b>       | <a href="#">SPEC SHEET</a> | 5000K | 1800   | T8           | 25   |
| 16.5   | DL25291328  | 4' 16.5WT8/40K/FR/DUAL POWER/SAFETY COATED/V5 - <b>CEE/DLC®</b> | <a href="#">SPEC SHEET</a> | 4000K | 2300   | T8           | 25   |
|  | DL25391329  | 4' 16.5WT8/50K/FR/DUAL POWER/SAFETY COATED/V5 - <b>CEE/DLC®</b> | <a href="#">SPEC SHEET</a> | 5000K | 2400   | T8           | 25   |
| 17   | DL25491141  | 4' 17WT8/35K/FR/DUAL POWER - <b>CEE/DLC®</b>                    | <a href="#">SPEC SHEET</a> | 3500K | 2200   | T8           | 25   |
|  | DL25591142  | 4' 17WT8/40K/FR/DUAL POWER - <b>CEE/DLC®</b>                    | <a href="#">SPEC SHEET</a> | 4000K | 2200   | T8           | 25   |
|  | DL25691143  | 4' 17WT8/50K/FR/DUAL POWER - <b>CEE/DLC®</b>                    | <a href="#">SPEC SHEET</a> | 5000K | 2200   | T8           | 25   |
| 18.5   | DL25791492  | 4' 18.5WT8/35K/FR/DUAL POWER/V6 - <b>DLC®</b>                   | <a href="#">SPEC SHEET</a> | 3500K | 2450   | T8           | 25   |
|  | DL25891493  | 4' 18.5WT8/40K/FR/DUAL POWER/V6 - <b>DLC®</b>                   | <a href="#">SPEC SHEET</a> | 4000K | 2600   | T8           | 25   |
|  | DL25991447  | 4' 18.5WT8/50K/FR/DUAL POWER/V6 - <b>DLC®</b>                   | <a href="#">SPEC SHEET</a> | 5000K | 2600   | T8           | 25   |
| <b>T8/SINGLE PIN</b>   |             |   |                            |       |        |              |      |
|  | DL26090744  | 8' 34WT8/40K/FR/SINGLE PIN - <b>DLC®</b>                        | <a href="#">SPEC SHEET</a> | 4000K | 4400   | T8           | 10   |
|  | DL26190745  | 8' 34WT8/50K/FR/SINGLE PIN - <b>DLC®</b>                        | <a href="#">SPEC SHEET</a> | 5000K | 4400   | T8           | 10   |
| 43   | DL26290740  | 8' 43WT8/40K/FR/SINGLE PIN - <b>DLC®</b>                        | <a href="#">SPEC SHEET</a> | 4000K | 5500   | T8           | 10   |
|  | DL26390741  | 8' 43WT8/50K/FR/SINGLE PIN - <b>DLC®</b>                        | <a href="#">SPEC SHEET</a> | 5000K | 5500   | T8           | 10   |
| <b>T8/RDC</b>  |             |   |                            |       |        |              |      |
|  | DL26490816  | 8' 43WT8/50K/FR/HO -  | <a href="#">SPEC SHEET</a> | 5000K | 5500   | T8           | 10   |
| <b>LED DIRECT WIRE SIGN LAMPS • 120-277V - UL TYPE B</b>                       |             |   |                            |       |        |              |      |
|  | DL26584999  | LED SIGN 30" 11WT8/65K/CL/HO/120-277V                           | <a href="#">SPEC SHEET</a> | 6500K | 1500   | T8           | 10   |
|  | DL26685001  | LED SIGN 42" 15WT8/65K/CL/HO/120-277V                           | <a href="#">SPEC SHEET</a> | 6500K | 2100   | T8           | 10   |
|  | DL26785003  | LED SIGN 48" 18WT8/65K/CL/HO/120-277V                           | <a href="#">SPEC SHEET</a> | 6500K | 2500   | T8           | 10   |
|  | DL26885005  | LED SIGN 60" 24WT8/65K/CL/HO/120-277V                           | <a href="#">SPEC SHEET</a> | 6500K | 3350   | T8           | 10   |
|  | DL26985007  | LED SIGN 64" 26WT8/65K/CL/HO/120-277V                           | <a href="#">SPEC SHEET</a> | 6500K | 3650   | T8           | 10   |
|  | DL27085009  | LED SIGN 72" 30WT8/65K/CL/HO/120-277V                           | <a href="#">SPEC SHEET</a> | 6500K | 4200   | T8           | 10   |
|  | DL27185011  | LED SIGN 84" 32WT8/65K/CL/HO/120-277V                           | <a href="#">SPEC SHEET</a> | 6500K | 4500   | T8           | 10   |
|  | DL27285013  | LED SIGN 96" 36WT8/65K/CL/HO/120-277V                           | <a href="#">SPEC SHEET</a> | 6500K | 5000   | T8           | 10   |
|  | DL27385015  | LED SIGN 108" 42WT8/65K/CL/HO/120-277V                          | <a href="#">SPEC SHEET</a> | 6500K | 5800   | T8           | 10   |
|  | DL27485017  | LED SIGN 117" 45WT8/65K/CL/HO/120-277V                          | <a href="#">SPEC SHEET</a> | 6500K | 6300   | T8           | 10   |



DIMM = DIMMABLE / **ES®** = ENERGY STAR®  
 FOR EXACT PART NUMBERS PLEASE CONTACT FACTORY